

Engineered to Perform



TX-5700E



TX-5700

TX-5700/5700E

Powerful Fanless POS Box

TX-5700 Series is the latest high-end fan-free POS Box. Incorporating leading CPU Technology - 6th/7th generation Intel® Skylake/Kaby Lake processor and supporting vPro™ and RAID function, TX-5700 Series provides unmatched performance while juggling multiple program with ease.

TX-5700/TX-5700E

Powerful Performance

With SSD and 6th/7th generation Intel Skylake/Kaby Lake, TX-5700 Series (Core i5 processor) is faster, cooler and more efficient. In conjunction with patented fan-free technology, it delivers the unparalleled performance at completely silent operation.

Compact Design

Small footprint design allows TX-5700 Series to be placed anywhere you need a Point of Service System.

Rich I/O Connectivity

Connect to a wide range of POS peripherals and options for greater productivity and flexibility to fit in your store environment.

Specification	TX-5700	TX-5700E
Processor	Intel Skylake Core i5-6500TE; Intel Kaby Lake Core i5-7500T	
System Memory	DDR4 SO-DIMM x 2, max. 32 GB	
Storage Device	SATA x 2+ M.2 x 1	
RAID Function	Optional 2nd SSD required	
Intel vPro Support	Yes	
TPM	Yes	
Power Supply	12V/84W	12V/150W
OS support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry 64 bit/Windows 10 IoT 64 bit for Skylake processor; Windows 10 IoT 64 bit for Kaby Lake processor	

I/O & Expansion

Serial Port	5, DB9 x 3, COM5/COM6 via optional cable from service window, 5V/12V support on all COM ports	
Parallel Port	N/A	
Standard USB Port	7, USB 3.0 x 4 + USB 2.0 x 3	USB 3.0 x 4
Powered USB Port	N/A	3, 24V x 1 +12V x 2
LAN Port	10/100/1000 Mb x 2	
Display Port	VGA x 1, 12V support for Posiflex monitors; HDMI x 1 + DVH	
CR Port	1, control 2 CR via optional Y-cable, support 24V	
PS/2 Port	N/A	
Audio	Internal 2W speaker x 1 + Mic-in/Line-out	
Expansion Slot	M.2 slot x 1	

Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 83
Weight (N. W. in kg)	2.75

Environmental

Operating Condition	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in Options

WiFi	M.2 WiFi/BT module
------	--------------------

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications



EN20210629V2

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller